



Technical data

Type	Cap-Base	Dim. no	Technical Lamp Wattage (W)	Lamp Voltage (V)	UVC at 100h (W)	Lamp Current (A)	Useful life (h)	Depreciation at useful life (%)	Packaging type	Packaging configuration	Ordering number 12 NC
TUV 36T5 HE SP	Single Pin	1	40	97	14.0	0.425	9000	15	UNP	32	927970004099
TUV 36T5 HO 4P SE	4 Pins Single Ended	2	75	97	23.0	0.800	9000	15	UNP	32	927972104099
TUV 36T5 HE 4P SE	4 Pins Single Ended	2	40	97	14.0	0.425	9000	15	UNP	32	927970204099
TUV 64T5 HE 2P SE	2 Pins Single Ended	3	75	178	29.0	0.425	9000	15	UNP	32	927970904099
TUV 64T5 HE 4P SE (Rapid Start)	4 Pins Single Ended	4	75	178	29.0	0.425	9000	15	UNP	32	927970704099
TUV 64T5 HE 4P SE (Instant Start)	4 Pins Single Ended	4	75	178	29.0	0.425	9000	15	UNP	32	927970804099
TUV 64T5 HO 4P SE	4 Pins Single Ended	4	140	175	45.0	0.800	9000	15	UNP	32	927971104099



Single Pin



2 Pins / 4 Pins Single Ended

Dim. no.	A max.	C max.	D max.
1	845.4	863.9	19

* Dimensions (mm)

Dim. no.	A max.	C max.	D max.
2	845.4	853.1	19
3	1556.6	1564.5	19
4	1556.6	1564.4	19